



LOAD CERTIFICATE: 7.50-18

Brand: ASCENSO

Tread Pattern : TSB 110

Ply Rating : 8

Tyre Construction: Bias

Type: Tube Type

Main Applications: 2 WD Tractor

TRA Code: F2



Salient Features

Wider Centre Rib:

Ease in steering & prevents damage to the grass land

High Strength Nylon Carcass:

Provides stability to the machine & ensures durability

Special Tread Compound:

Provides longer tyre life
Resistance to puncture



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Inflation Pressure	Recommend load, kg (lbs)										
		SW	OD					Speed, km/h(mph)										
		mm	mm	mm	mm		Mixed Application											
		in	in	in	in		Bar	Static	10	20	25	30	40					
				Psi	6	12	15		20	25								
7.50-18	5.50F	203	859	395	2570	8PR	2.9	2160	1440	990	920	800	720					
							42	4760	3170	2180	2030	1760	1590					
							3.2	2280	1520	1050	970	840	760					
							46	5020	3350	2310	2140	1850	1670					
							8.0	33.8	15.6	101.2	102 A8	3.5	2400	1600	1100	1020	890	800
							51	5290	3520	2420	2250	1960	1760					
							3.85	2550	1700	1170	1090	940	850					
							56	5620	3740	2580	2400	2070	1870					

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification