



LOAD CERTIFICATE: 7.50-20

Brand: ASCENSO

Tread Pattern : TSB 110

Ply Rating : 8

Tyre Construction: Bias

Type: Tube Type

Main Applications: 2 WD Tractor

TRA Code: F2



Salient Features

Wider Centre Rib:

Ease in steering & prevents damage to the grass land

High Strength Nylon Carcass:

Provides stability to the machine & ensures durability

Special Tread Compound:

Provides longer tyre life
Resistance to puncture



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Inflation Pressure	Recommend load, kg (lbs)					
		SW	OD					Speed, km/h(mph)					
		mm	mm	Mixed Application									
		in	in	mm	mm		Bar	Static	10	20	25	30	40
mm	mm	in	in	Psi	6	12	15		20	25			
7.50-20	5.50F	203	909	420	2719	8PR	2.9	2340	1560	1080	1000	870	780
							42	5150	3440	2380	2200	1920	1720
							3.2	2490	1660	1150	1060	920	830
							46	5480	3660	2530	2330	2030	1830
		8.0	35.8	16.5	107.0	105 A8	3.5	2610	1740	1200	1110	970	870
							51	5750	3830	2640	2440	2140	1920
							3.85	2780	1850	1280	1180	1030	925
							56	6120	4070	2820	2600	2270	2040

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover