



LOAD CERTIFICATES: 800/70 R38

Brand: ASCENSO

Tread Pattern : XLR 880

Tyre Construction: Radial

LSI : 178 D

Type: Tube Less

Main Applications: 4WD Tractor

TRA Code : R-1W



Salient Features

Optimum Tread Design:

Maximum performance in field and on road operations

First in the Industry with Dual Mud Breakers:

Ensure better self-cleaning and Maximum traction

Greater Lug Overlap:

Provides safe and comfortable ride at high speeds



SizeW167L	Rim	Unloaded Dimension		SLR	RC	Load Index PR Symbols	Inflation Pressure	Recommended load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
				Mixed application										
		mm	mm	mm	mm			Bar	Static	10	25	30	40	50
in	in	in	in	Psi		6	16	19	25	31	40			
800/70 R 38	DW25B	798 31.4	2085 82.1	945 37.2	6236 245.5	178 D	0.8	9380	6120	4830	4690	4470	4280	4080
							12	20660	13480	10640	10330	9850	9430	8990
							1.2	12050	7860	6210	6030	5740	5500	5240
							17	26540	17310	13680	13280	12640	12110	11540
							1.6	14720	9600	7580	7360	7010	6720	6400
							23	32420	21150	16700	16210	15440	14800	14100
							2.0	16170	10550	8330	8080	7700	7380	7030
							29	35620	23240	18350	17800	16960	16260	15480
							2.4	17250	11250	8890	8630	8210	7880	7500
							35	38000	24780	19580	19010	18080	17360	16520

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Pvt. Ltd.

612, 6th Floor, Maker Chambers IV, Nariman Point, Mumbai 400021, Maharashtra, India

T: +91 22 4348 1600 Website: www.ascensotyres.com