



# LOAD CERTIFICATES: 600/65 R 28

**Brand:** ASCENSO

**Tread Pattern :** XLR 880

**Tyre Construction:** Radial

**LSI :** 154 D

**Type:** Tube Less

**Main Applications:** 4WD Tractor

**TRA Code :** R-1W



## Salient Features

### **Optimum Tread Design:**

Maximum performance in field and on road operations

### **First in the Industry with Dual Mud Breakers:**

Ensure better self-cleaning and Maximum traction

### **Greater Lug Overlap:**

Provides safe and comfortable ride at high speeds



# Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	Load Index PR Symbols	Inflation Pressure	Recommended load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
								Mixed application						
								Bar	Static	10	25	30	40	50
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm		
in	in	in	in	in	in	in	Psi	6	16	19	25	31	40	
600/65 R 28	DW20B	611 24.1	1491 58.7	677 26.7	4459 175.6	154 D	1.2	5180	3380	2670	2590	2460	2360	2250
							17	11410	7440	5880	5700	5420	5200	4960
							1	5750	3750	2960	2880	2740	2630	2500
							20	12670	8260	6520	6340	6040	5790	5510
							1.7	6620	4320	3410	3310	3150	3020	2880
							25	14580	9520	7510	7290	6940	6650	6340
							2.1	7770	5070	4010	3890	3700	3550	3380
							30	17110	11170	8830	8570	8150	7820	7440
							2.4	8630	5630	4440	4310	4110	3940	3750
35	19010	12400	9780	9490	9050	8680	8260							

**Note:** All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Pvt. Ltd.

612, 6<sup>th</sup> Floor, Maker Chambers IV, Nariman Point, Mumbai 400021, Maharashtra, India

T: +91 22 4348 1600 Website: [www.ascensotyres.com](http://www.ascensotyres.com)