



LOAD CERTIFICATES: 560/45R22.5 (SB)

Brand: ASCENSO

Tread Pattern : FTR 170

Tyre Construction: Radial

LSI : 152 D

Type: Tube Less

Main Applications: Implements, Trailers, Slurry Tankers and Dump Trailer

TRA Code : IMP



Salient Features

Steel Belted Directional Tread for Superior Traction:

- Homogenous Pattern for On Road and Farm Applications
- Tyres Designed for High load and Speed Operations.
- Ensure traction and self-cleaning during field operation.
- Enhanced Roadability ensuring Better Mileage.



Technical Specification

Size	Rim	Unloaded Dimension		Static Load Radius	Rolling Circumference	Load Index / Speed Index	Inflation Pressure	Recommended load, kg (lbs)						
		Speed, km/h (mph)												
		Mixed application												
		bar	Static					10	25	30	40	50	65	
psi		6	16	19	25	31	40							
mm	mm	mm	mm	mm	mm	mm	mm							
in	in	in	in	in	in	in	in							
560/45R22.5 (SB)	AG16.00	543 21.4	1075 42.3	493 19.4	3215 126.6	152 D	2.4	5450	4270	3740	3580	3220	2870	2370
							35	12000	9410	8240	7890	7090	6320	5220
							2.8	6190	4840	4250	4060	3660	3250	2690
							41	13630	10660	9360	8940	8060	7160	5930
							3.2	6810	5330	4680	4470	4030	3580	2960
							46	15000	11740	10310	9850	8880	7890	6520
							3.6	7480	5850	5140	4910	4420	3930	3250
							52	16480	12890	11320	10810	9740	8660	7160
							4	8170	6390	5610	5360	4830	4300	3550
							58	18000	14070	12360	11810	10640	9470	7820

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Private Limited, 3rd Floor, Peninsula Chambers, Peninsula Corporate Park, G K Marg, Lower Parel West, Mumbai Maharashtra - 400013, India.

T: +91 22 4348 1600 Website: www.ascensotyres.com