



LOAD CERTIFICATES: 600/55R26.5 (SB)

Brand: ASCENSO

Tread Pattern : FTR 170

Tyre Construction: Radial

LSI : 165 D

Type: Tube Less

Main Applications: Implements, Trailers, Slurry Tankers and Dump Trailer

TRA Code : IMP



Salient Features

Steel Belted Directional Tread for Superior Traction:

- Homogenous Pattern for On Road and Farm Applications
- Tyres Designed for High load and Speed Operations.
- Ensure traction and self-cleaning during field operation.
- Enhanced Roadability ensuring Better Mileage.



Technical Specification

Size	Rim	Unloaded Dimension		Static Load Radius	Rolling Circumference	Load Index / Speed Index	Inflation Pressure	Recommended load, kg (lbs)						
								Speed, km/h (mph)						
		SW	OD	mm	mm			Mixed application						
		mm	mm					bar	Static	10	25	30	40	50
in	in	in	in	psi		6	16	19	25	31	40			
600/55R26.5 (SB)	AG20.00	611 24.1	1333 52.5	609 24.0	3987 157.0	165 D	2.4	7800	6100	5360	5120	4610	4100	3390
							35	17180	13440	11810	11280	10150	9030	7470
							2.8	8860	6930	6080	5810	5240	4660	3850
							41	19520	15260	13390	12800	11540	10260	8480
							3.2	9730	7610	6680	6390	5750	5120	4230
							46	21430	16760	14710	14070	12670	11280	9320
							3.6	10670	8350	7330	7010	6310	5610	4640
							52	23500	18390	16150	15440	13900	12360	10220
							4	11850	9270	8140	7780	7000	6230	5150
58	26100	20420	17930	17140	15420	13720	11340							

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover.

Mahansaria Tyres Private Limited, 3rd Floor, Peninsula Chambers, Peninsula Corporate Park, G K Marg, Lower Parel West, Mumbai Maharashtra - 400013, India.

T: +91 22 4348 1600 Website: www.ascensotyres.com