



LOAD CERTIFICATES: 650/55R26.5 (SB)

Brand: ASCENSO

Tread Pattern : FTR 170

Tyre Construction: Radial

LSI : 170 D

Type: Tube Less

Main Applications: Implements, Trailers, Slurry Tankers and Dump Trailer

TRA Code : IMP



Salient Features

Steel Belted Directional Tread for Superior Traction:

- Homogenous Pattern for On Road and Farm Applications
- Tyres Designed for High load and Speed Operations.
- Ensure traction and self-cleaning during field operation.
- Enhanced Roadability ensuring Better Mileage.



Technical Specification

Size	Rim	Unloaded Dimension		Static Load Radius	Rolling Circumference	Load Index / Speed Index	Inflation Pressure	Recommended load, kg (lbs)							
								Speed, km/h (mph)							
		SW	OD	mm	mm	mm	mm	bar	Mixed application						
		mm	mm						Static	10	25	30	40	50	65
		in	in						in	in	psi	6	16	19	25
650/55R26.5 (SB)	AG20.00	645 25.4	1389 54.7	632 24.9	4154 163.5	170 D	2.4	8860	6930	6080	5810	5240	4660	3850	
							35	19520	15260	13390	12800	11540	10260	8480	
							2.8	10030	7850	6890	6580	5930	5280	4360	
							41	22090	17290	15180	14490	13060	11630	9600	
							3.2	11040	8640	7580	7250	6530	5810	4800	
							46	24320	19030	16700	15970	14380	12800	10570	
							3.6	12120	9490	8330	7960	7170	6380	5270	
							52	26700	20900	18350	17530	15790	14050	11610	
							4	13800	10800	9480	9060	8160	7260	6000	
							58	30400	23790	20880	19960	17970	15990	13220	

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Private Limited, 3rd Floor, Peninsula Chambers, Peninsula Corporate Park, G K Marg, Lower Parel West, Mumbai Maharashtra - 400013, India.

T: +91 22 4348 1600 Website: www.ascensotyres.com