



560/60R22.5 GSP+

Inch	22.5"
Tyre Size	560/60R22.5
Tread Pattern	GSP+
PR/LI	173A8/170D
Tread Pattern Depth	22 mm
Overall Diameter	1255 mm
Section Width	560 mm
Static Loading Radius	615 mm
Load Capacity	6500 kg
Inflation Pressure	6 bar
Speed Limit	40 km/h
Type (New or Remould)	Remould
Rim Size	W16x22.5/5p°

Load/speed index

Snelheid (km/h)	0	10	25	30	40	65
Draagvermogen (kg)	14100	10100	7600	7000	6500	6000

Alle gegevens volgens ETRTO normen. Mag niet gekopieerd en/of verspreid worden zonder schriftelijke toestemming van Hollandse Bandenmarkt Internationaal BV



Hoofdkantoor

Hollandse Bandenmarkt Internationaal BV

Stevinweg 25 • 4691 SM Tholen • The Netherlands

T +31 (0)166 60 10 40 • F +31 (0)166 60 10 41 • info@hbi-tyres.com

Wilt
u meer
informatie?
Bel of mail ons.

www.hbi-tyres.com



ISO 9001:2008
gecertificeerd



560/60R22.5 GSP+



Inch	22.5"
Tyre Size	560/60R22.5
Tread Pattern	GSP+
PR/LI	173A8/170D
Tread Pattern Depth	22 mm
Overall Diameter	1255 mm
Section Width	560 mm
Static Loading Radius	615 mm
Load Capacity	6500 kg
Inflation Pressure	6 bar
Speed Limit	40 km/h
Type (New or Remould)	Remould
Rim Size	W16x22.5/5p°

