

FARMAX R65

FEATURES

- Greater lug overlap
- More lugs in footprint

BENEFITS

- Improved roadability for haulage
- Safe and comfortable ride
- Less vibration on road

FEATURES

- Mud breaker
- Variable groove contour
- Smooth flowing step groove

BENEFITS

- Better self cleaning properties
- Less soil from field to road



FEATURE

- R1-W tread depth

BENEFIT

- Long service life

FEATURES

- Lower lug angle at shoulder
- Higher lug angle at centre

BENEFITS

- Better traction
- Better ride

FEATURE

- Rounded shoulder

BENEFIT

- Reduced soil disturbance


FEATURE

- Wider tread

BENEFITS

- Lower soil compaction
- Increased footprint area

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph / mph							
				SW	OD				Non cyclic operation				Cyclic operation			
				mm	mm				25	40	50	65	bar	10	15	
				in	in				16	25	31	40	psi	6	9	
650/65R38	157D	TL	DW20B	645	1811	825	5489	0.8	3160	3260	3010	2890	2750	0	0	0
								12	6960	7180	6630	6370	6060	0	0	0
								1	3600	3710	3430	3290	3130	1.25	5320	4850
								15	7930	8170	7560	7250	6890	18	11720	10680
								1.3	4200	4330	4000	3830	3650	1.63	6210	5660
								19	9250	9540	8810	8440	8040	24	13680	12470
								1.6	4740	4890	4520	4330	4125	2	7010	6390
								23	10440	10770	9960	9540	9090	29	15440	14070

All tires confirms ETRTO T&RA & STRO standards