

# FARMAX R65

**FEATURES**

- Greater lug overlap
- More lugs in footprint

**BENEFITS**

- Improved roadability for haulage
- Safe and comfortable ride
- Less vibration on road

**FEATURES**

- Mud breaker
- Variable groove contour
- Smooth flowing step groove

**BENEFITS**

- Better self cleaning properties
- Less soil from field to road



**FEATURE**

- R1-W tread depth

**BENEFIT**

- Long service life

**FEATURES**

- Lower lug angle at shoulder
- Higher lug angle at centre

**BENEFITS**

- Better traction
- Better ride

**FEATURE**

- Rounded shoulder

**BENEFIT**

- Reduced soil disturbance


**FEATURE**

- Wider tread

**BENEFITS**

- Lower soil compaction
- Increased footprint area

## MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph / mph							
				SW	OD				Non cyclic operation				Cyclic operation			
				mm	mm				Static	25	40	50	65	bar	10	15
				in	in				16	25	31	40	psi	6	9	
650/65R42	158D	TL	DW20B W18L	645 25.4	1913 75.3	885 34.8	5778 227.5	0.8	3250	3350	3100	2970	2830	1	4810	4390
								12	7160	7380	6830	6540	6230	15	10590	9670
								1	3710	3830	3540	3390	3230	1.25	5490	5010
								15	8170	8440	7800	7470	7110	18	12090	11040
								1.3	4320	4460	4120	3950	3760	1.63	6390	5830
								19	9520	9820	9070	8700	8280	24	14070	12840
								1.6	4890	5040	4650	4460	4250	2	7230	6590
								23	10770	11100	10240	9820	9360	29	15930	14520

All tires confirms ETRTO T&RA & STRO standards