

# FARMAX RC

**FEATURES**

- High lug angle at centre
- More overlap at centre

**BENEFITS**

- Better roadability
- Better stability

**FEATURE**

- Rounded shoulder

**BENEFIT**

- Soil and plant protection

**FEATURE**

- Deep tread pattern

**BENEFIT**

- Long service life




**FEATURES**

- D-Rated tyres with maximum speed up to 40 MPH
- Strong nylon carcass and strong bead

**BENEFITS**

- Better roadability even at higher speed
- Better lateral and radial stability
- Minimum chances of any mechanical failure

## MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph / mph						
				SW	OD				Field	10	25	40	50	65	70
				mm in	mm in					6	16	25	31	40	50
270/95R36 (11.2R36)	136D/ 139A8	TL	W8 W9 W10	275 10.8	1427 56.2	670 26.4	4349 171.2	2.8	2090	2730	2160	1990	1910	1820	1660
								41	4600	6010	4760	4380	4210	4010	3660
								3.6	2430	3170	2500	2310	2220	2110	1920
								52	5350	6980	5510	5090	4890	4650	4230
								4	2580	3360	2650	2450	2350	2240	2040
								58	5680	7400	5840	5400	5180	4930	4490

All tires confirms ETRTO T&RA & STRO standards