

# FARMAX R65

**FEATURES**

- Greater lug overlap
- More lugs in footprint

**BENEFITS**

- Improved roadability for haulage
- Safe and comfortable ride
- Less vibration on road

**FEATURES**

- Mud breaker
- Variable groove contour
- Smooth flowing step groove

**BENEFITS**

- Better self cleaning properties
- Less soil from field to road



**FEATURE**

- R1-W tread depth

**BENEFIT**

- Long service life

**FEATURES**

- Lower lug angle at shoulder
- Higher lug angle at centre

**BENEFITS**

- Better traction
- Better ride

**FEATURE**

- Rounded shoulder

**BENEFIT**

- Reduced soil disturbance


**FEATURE**

- Wider tread

**BENEFITS**

- Lower soil compaction
- Increased footprint area

## MACHINERY



Tractor

Size	LI/SS	Rim	Unloaded dimension		SLR	RC	Infl. Press	Speed, km/h (mph)							
			SW	OD				Non cyclic operation				Cyclic operation			
								Static	25	40	50	65	bar	10	15
			mm/in	mm/in				mm/in	mm/in	mm/in	mm/in	bar	psi	6	9
600/65R30	155D	DW20B W18L	611 24.1	1542 60.7	693 27	4626 182	1.8	3760	3870	3580	3430	3270	2.25	5560	5070
							26	8280	8520	7890	7560	7200	33	12250	11170
							2	4000	4120	3810	3650	3480	2.5	5920	5390
							29	8810	9070	8390	8040	7670	36	13040	11870
							2.2	4230	4360	4030	3860	3680	2.75	6260	5700
							32	9320	9600	8880	8500	8110	40	13790	12560
							2.4	4460	4590	4240	4070	3875	3	6590	6010
							35	9820	10110	9340	8960	8540	44	14520	13240

All tires confirms ETRTO T&RA & STRO standards