

# FARMAX R70

**FEATURE**

- Greater lug overlap

**BENEFITS**

- More lugs in footprint
- Better stability

**FEATURE**

- Larger inner volume

**BENEFITS**

- Reduced soil compaction
- Increased load carrying capacity



**FEATURES**

- Reduced space between lugs
- Mud breaker at the centre

**BENEFITS**

- Better roadability
- Increased service life
- Self cleaning

**FEATURE**

- Rounded shoulder

**BENEFIT**

- Less soil disturbance

**FEATURE**

- Dual lug angle

**BENEFITS**

- Superior traction
- Better Roadability


**FEATURE**

- Wider tread

**BENEFITS**

- Reduced soil compaction
- Increased footprint

## MACHINERY



Tractor

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circum	PR, Load Index	Infl. Press	Recommend load, kg (lbs)					
		SW	OD					Speed, km/h (mph)					
		mm / in	mm / in					Speed	10	20	30	40	50
580/70R42	W 18 L	580 22.8	1879 74	859 33.8	5578 219.6	158A8/B	bar	Satatic	10	20	30	40	50
							psi	6	12	19	25	31	
							0.8	6510	4250	3480	3030	2830	2830
							1.2	8260	5390	4420	3840	3590	3590
							1.7	18190	11870	9740	8460	7910	7910
							1.3	8650	5640	4620	4020	3760	3760
							1.9	19050	12420	10180	8850	8280	8280
							1.6	9780	6380	4720	4550	4250	4250
2.3	21540	14050	10400	10020	9360	9360							

All tires confirms ETRTO T&RA & STRO standards