

LIFT PRO

FEATURE

- Unique R1 pattern

BENEFIT

- Excellent traction



FEATURE

- Deep under tread

BENEFIT

- Improved puncture resistance


FEATURE

- Strong nylon casing and thick sidewall

BENEFIT

- High radial and lateral stability

MACHINERY



Telehandler

Size	LI/SS	Type	Rim	Unloaded dimension		SLR	RC	Infl. Press	Recommended load kg(lbs)						Speed		Kmph mph
				SW	OD				Speed Kmph (mph)						Cyclic Operations		
									Non cyclic operation						10	15	
				mm / in	mm / in				mm / in	mm / in	mm / in	mm / in	mm / in	mm / in	mm / in	mm / in	
460/70R24	159A8/B	TL	W15L W16L	455 17.9	1254 49.4	566 22.3	3713 146	bar									
								psi									
								2.4	7430	4040	3520	3360	3230	3230	4850	4330	
								3.5	16370	8900	7750	7400	7110	46835	10680	9540	
								2.8	8140	4430	3860	3680	3540	3540	5310	4740	
								4.1	17930	9760	8500	8110	7800	51330	11700	10440	
								3	8490	4610	4020	3840	3690	3690	5540	4940	
								4.4	18700	10150	8850	8460	8130	53505	12200	10880	
								3.6	9450	5140	4480	4270	4110	4110	6170	5510	
								5.2	20810	11320	9870	9410	9050	59595	13590	12140	
								4	10060	5470	4770	4550	4375	4375	6560	5860	
								5.8	22160	12050	10510	10020	9640	63437.5	14450	12910	

All tires confirms ETRTO T&RA & STRO standards