

LOADPRO



FEATURE

Greater lug overlap and more lugs in footprint

BENEFIT

Uniform load distribution

FEATURE

Extra reinforced Sidewalls

BENEFIT

Additional lateral stability

FEATURE

Steel belted radial construction

BENEFIT

Protection from Punctures


FEATURE

Strong bead

BENEFIT

Better carcass strength and load carrying capacity

MACHINERY



Telehandler

Size	Rim	Unloaded dimension		Static Loaded	Rolling Circum	Load Index	Infl. press.	Recommend load, kg (lbs)							
		SW	OD	Radius	Speed	bar		Speed, km/h (mph)							
		mm	mm	mm				Static	Constant load					Cyclic operation	
		in	in	in					6	12	19	25	31	6	9
460 70R24 SB*	W15L	455	1254	566	3713		159 A8/B	0.8	3930	2140	1860	1780	1710	1710	2570
	12					8660		4710	4100	3920	3770	24795	5660	5040	
	1.6					5890		3200	2790	2660	2560	2560	3840	3430	
	23	12970	7050	6150	5860	5640		37120	8460	7560					
	2.8	8170	4440	3870	3690	3550		3550	5330	4760					
	41	18000	9780	8520	8130	7820		51475	11740	10480					
	3.2	8830	4800	4190	3990	3840		3840	5760	5150					
	46	19450	10570	9230	8790	8460		55680	12690	11340					
	4	10060	5470	4770	4550	4375		4375	6560	5860					
58	22160	12050	10510	10020	9640	63437.5	14450	12910							

* SB - Steel belted

All tires confirms ETRTO T&RA & STRO standards