



10.0/75 - 15.3 10 AS-Impl 02 TL

Cultor implement tyres are designed for their specific main application. All profiles unify the following benefits:

- Long service life through low-wear tread compound
- High puncture resistance by optimised construction

TECHNICAL DATA

Tyre size	10.0/75 - 15.3	Tread Pattern	AS-Impl 02
Tyre size alternative	-	Ply rating	10
Service description LI SS	-	Type	TL
Tube	-	Permitted Rims	9.00x15.3
Section Width (mm)	264	Overall Diameter (mm)	780
Loaded Static Radius (mm)	360	Rolling Circumference (mm)	2 295
EAN code	8590341064066		

LOAD CAPACITY PER TIRE -

Tyre load at pressure (BAR)						Speed (km/h)
2,5	2,75	3	3,25	3,5	4	-
1 665	1 755	1 850	1 910	1 975	2 100	10
1 500	1 580	1 665	1 720	1 775	1 890	20
1 335	1 405	1 480	1 530	1 580	1 680	30
1 190	1 255	1 320	1 365	1 410	1 500	40
1 070	1 130	1 190	1 230	1 270	1 350	50

LOAD CAPACITY PER TIRE -

Tyre load at pressure (BAR)						Speed (km/h)
2,5	2,75	3	3,25	3,5	4	-
1 210	1 275	1 330	1 380	1 430	1 525	10
1 090	1 145	1 195	1 240	1 285	1 375	20
970	1 020	1 065	1 105	1 140	1 220	30
865	910	950	985	1 020	1 090	40
780	820	855	885	920	980	50