



280/85 R 24 115 A8 (112 B) RD-01 TL

- All-round standard tyres for a wide range of applications
- Balanced combination of features for various agricultural applications
- Very good grip and traction with much less slip
- Long service life thanks to the wear-resistant tread compound
- Large ground contact patch and lower operating pressure for less soil compaction

TECHNICAL DATA

Tyre size	280/85 R 24	Tread Pattern	RD-01
Tyre size alternative	11.2 R 24	Service description LI SS	115 A8 (112 B)
Type	TL	Permitted Rims	W 9 W 10
Section Width (mm)	290 300	Overall Diameter (mm)	1 105
Loaded Static Radius (mm)	498	Rolling Circumference (mm)	3 300
Speed radius index	525	EAN code	8590341099211
Water 75% (l)	85		

LOAD CAPACITY PER TIRE

Tyre load at pressure (BAR)											Speed (km/h)
0,6	0,8	1	1,2	1,4	1,6	2	2,4	3	4	4,4	-
-	-	890	970	1 040	1 120	-	-	-	-	-	50
-	890	980	1 070	1 140	1 215	-	-	-	-	-	40
850	960	1 050	1 140	1 220	1 300	-	-	-	-	-	30
1 030	1 160	1 280	1 390	1 490	1 580	1 825	-	-	-	-	10