



280/85 R 28 118 A8 (115 B) RD-01 TL

- All-round standard tyres for a wide range of applications
- Balanced combination of features for various agricultural applications
- Very good grip and traction with much less slip
- Long service life thanks to the wear-resistant tread compound
- Large ground contact patch and lower operating pressure for less soil compaction

TECHNICAL DATA

| | | | |
|----------------------------------|-------------|-----------------------------------|----------------|
| Tyre size | 280/85 R 28 | Tread Pattern | RD-01 |
| Tyre size alternative | 11.2 R 28 | Service description LI SS | 118 A8 (115 B) |
| Type | TL | Permitted Rims | W 9 W 10 |
| Section Width (mm) | 288 298 | Overall Diameter (mm) | 1 190 |
| Loaded Static Radius (mm) | 551 | Rolling Circumference (mm) | 3 582 |
| Speed radius index | 575 | EAN code | 8590341099242 |
| Water 75% (l) | 100 | | |

LOAD CAPACITY PER TIRE

| Tyre load at pressure (BAR) | | | | | | | | | | | Speed (km/h) |
|-----------------------------|-------|-------|-------|-------|-------|-------|-----|---|---|-----|--------------|
| 0,6 | 0,8 | 1 | 1,2 | 1,4 | 1,6 | 2 | 2,4 | 3 | 4 | 4,4 | - |
| - | - | 965 | 1 045 | 1 125 | 1 215 | - | - | - | - | - | 50 |
| - | 965 | 1 060 | 1 150 | 1 235 | 1 320 | - | - | - | - | - | 40 |
| 920 | 1 030 | 1 135 | 1 230 | 1 320 | 1 410 | - | - | - | - | - | 30 |
| 1 120 | 1 255 | 1 380 | 1 495 | 1 605 | 1 715 | 1 980 | - | - | - | - | 10 |