



320/85 R 32 142 A8 (142 B) RD-01 TL

- All-round standard tyres for a wide range of applications
- Balanced combination of features for various agricultural applications
- Very good grip and traction with much less slip
- Long service life thanks to the wear-resistant tread compound
- Large ground contact patch and lower operating pressure for less soil compaction

TECHNICAL DATA

Tyre size	320/85 R 32	Tread Pattern	RD-01
Tyre size alternative	12.4 R 32	Service description LI SS	142 A8 (142 B)
Type	TL	Permitted Rims	W 9 W 11 W 10
Section Width (mm)	305 325 315	Overall Diameter (mm)	1 385
Loaded Static Radius (mm)	637	Rolling Circumference (mm)	4 130
Speed radius index	650	EAN code	8590341099525
Water 75% (l)	140		

LOAD CAPACITY PER TIRE

Tyre load at pressure (BAR)											Speed (km/h)
0,6	0,8	1	1,2	1,4	1,6	2	2,4	3	4	4,4	-
-	-	-	1 400	1 555	1 710	1 880	2 000	2 280	2 650	-	50
-	1 150	1 280	1 400	1 555	1 710	1 880	2 000	2 280	2 650	-	40
-	1 235	1 370	1 500	1 665	1 830	2 010	2 140	2 440	2 835	-	30
-	1 615	1 795	1 960	2 180	2 395	2 630	2 800	2 800	3 710	3 875	10