



340/85 R 24 125 A8 (122 B) RD-01 TL

- All-round standard tyres for a wide range of applications
- Balanced combination of features for various agricultural applications
- Very good grip and traction with much less slip
- Long service life thanks to the wear-resistant tread compound
- Large ground contact patch and lower operating pressure for less soil compaction

TECHNICAL DATA

Tyre size	340/85 R 24	Tread Pattern	RD-01
Tyre size alternative	13.6 R 24	Service description LI SS	125 A8 (122 B)
Type	TL	Permitted Rims	W 12 W 11
Section Width (mm)	365 355	Overall Diameter (mm)	1 186
Loaded Static Radius (mm)	530	Rolling Circumference (mm)	3 530
Speed radius index	575	EAN code	8590341099327
Water 75% (l)	140		

LOAD CAPACITY PER TIRE

Tyre load at pressure (BAR)											Speed (km/h)
0,6	0,8	1	1,2	1,4	1,6	2	2,4	3	4	4,4	-
-	-	1 205	1 305	1 400	1 500	-	-	-	-	-	50
-	1 205	1 325	1 435	1 540	1 650	-	-	-	-	-	40
1 145	1 290	1 420	1 535	1 650	1 765	-	-	-	-	-	30
1 395	1 565	1 720	1 870	2 005	2 145	2 475	-	-	-	-	10