



# 340/85 R 28 127 A8 (124 B) RD-01 TL

- All-round standard tyres for a wide range of applications
- Balanced combination of features for various agricultural applications
- Very good grip and traction with much less slip
- Long service life thanks to the wear-resistant tread compound
- Large ground contact patch and lower operating pressure for less soil compaction

## TECHNICAL DATA

Tyre size	340/85 R 28	Tread Pattern	RD-01
Tyre size alternative	13.6 R 28	Service description LI SS	127 A8 (124 B)
Type	TL	Permitted Rims	W 12 W 11
Section Width (mm)	367 357	Overall Diameter (mm)	1 292
Loaded Static Radius (mm)	-	Rolling Circumference (mm)	-
Speed radius index	625	EAN code	8590341099266
Water 75% (l)	160		

## LOAD CAPACITY PER TIRE

Tyre load at pressure (BAR)											Speed (km/h)
0,6	0,8	1	1,2	1,4	1,6	2	2,4	3	4	4,4	-
-	-	1 295	1 400	1 505	1 600	-	-	-	-	-	50
-	1 295	1 425	1 540	1 655	1 750	-	-	-	-	-	40
1 230	1 380	1 520	1 650	1 770	1 875	-	-	-	-	-	30
1 500	1 680	1 850	2 005	2 150	2 275	2 625	-	-	-	-	10