



## 340/85 R 36 132 A8 (129 B) RD-01 TL

- All-round standard tyres for a wide range of applications
- Balanced combination of features for various agricultural applications
- Very good grip and traction with much less slip
- Long service life thanks to the wear-resistant tread compound
- Large ground contact patch and lower operating pressure for less soil compaction

### TECHNICAL DATA

<b>Tyre size</b>	340/85 R 36	<b>Tread Pattern</b>	RD-01
<b>Tyre size alternative</b>	13.6 R 36	<b>Service description LI SS</b>	132 A8 (129 B)
<b>Type</b>	TL	<b>Permitted Rims</b>	W 12 W 11
<b>Section Width (mm)</b>	365 355	<b>Overall Diameter (mm)</b>	1 493
<b>Loaded Static Radius (mm)</b>	682	<b>Rolling Circumference (mm)</b>	4 500
<b>Speed radius index</b>	725	<b>EAN code</b>	8590341099563
<b>Water 75% (l)</b>	195		

### LOAD CAPACITY PER TIRE

Tyre load at pressure (BAR)											Speed (km/h)
0,6	0,8	1	1,2	1,4	1,6	2	2,4	3	4	4,4	-
-	1 335	1 465	1 585	1 710	1 850	-	-	-	-	-	50
-	1 465	1 610	1 745	1 880	2 000	-	-	-	-	-	40
1 395	1 570	1 725	1 865	2 010	2 140	-	-	-	-	-	30
1 695	1 905	2 095	2 265	2 440	2 600	3 000	-	-	-	-	10