



380/85 R 34 146 A8 (143 B) RD-01 TL

- All-round standard tyres for a wide range of applications
- Balanced combination of features for various agricultural applications
- Very good grip and traction with much less slip
- Long service life thanks to the wear-resistant tread compound
- Large ground contact patch and lower operating pressure for less soil compaction

TECHNICAL DATA

Tyre size	380/85 R 34	Tread Pattern	RD-01
Tyre size alternative	14.9 R 34	Service description LI SS	146 A8 (143 B)
Type	TL	Permitted Rims	W 12 W 13 W 11
Section Width (mm)	401 411 391	Overall Diameter (mm)	1 538
Loaded Static Radius (mm)	691	Rolling Circumference (mm)	4 577
Speed radius index	-	EAN code	8590341099778
Water 75% (l)	-		

LOAD CAPACITY PER TIRE

Tyre load at pressure (BAR)									Speed (km/h)
0,6	0,8	1	1,2	1,4	1,6	2	2,4	3	-
-	-	1 680	2 005	2 150	2 290	2 535	3 000	-	50
-	1 680	1 850	2 005	2 150	2 290	2 535	3 000	-	40
1 600	1 800	1 980	2 145	2 300	2 450	2 710	3 210	-	30
1 945	2 185	2 405	2 610	2 795	2 970	3 295	3 900	4 500	10
-	1 478	1 628	1 764	1 892	2 015	2 231	2 640	-	40 Dual