



# 420/65 R 24 126 D (129 A8) RD-03 TL

- Reduced soil compaction thanks to large ground contact area and optimal pressure distribution
- Up to 40% higher tension force compared to standard tyres
- High load capacity due to the wide design and the large volume of air
- Outstanding grip and tractive force ensure less slip and much lower fuel consumption
- Maximum speed of 65 km/h on roads, high driving comfort and easy handling

## TECHNICAL DATA

Tyre size	420/65 R 24	Tread Pattern	RD-03
Service description LI SS	126 D (129 A8)	Type	TL
Permitted Rims	W 13 L W 12 W 11	Section Width (mm)	420 410 400
Overall Diameter (mm)	1 147	Loaded Static Radius (mm)	515
Rolling Circumference (mm)	3 425	Speed radius index	550
EAN code	8590341100825	Water 75% (l)	165

## LOAD CAPACITY PER TIRE

Tyre load at pressure (BAR)										Speed (km/h)
0,4	0,6	0,8	1	1,2	1,4	1,6	2	2,4	3	-
-	-	-	1 305	1 425	1 565	1 700	-	-	-	65
-	-	1 235	1 370	1 495	1 645	1 785	-	-	-	50
-	1 130	1 285	1 430	1 560	1 715	1 850	-	-	-	40
-	1 190	1 350	1 500	1 640	1 800	1 955	-	-	-	30
1 240	1 450	1 645	1 825	1 995	2 190	2 380	2 790	-	-	10