



## 420/70 R 24 130 A8 (130 B) RD-02 TL

- Reduced ground compression thanks to a larger ground contact area
- Excellent transmission of power due to greater grip and traction
- High load capacity with stable and safe handling on the road
- Improved driving comfort due to flexible sidewalls
- Longer service life coupled with reduced fuel consumption for low operational costs

### TECHNICAL DATA

<b>Tyre size</b>	420/70 R 24	<b>Tread Pattern</b>	RD-02
<b>Service description LI SS</b>	130 A8 (130 B)	<b>Type</b>	TL
<b>Permitted Rims</b>	W 12 W 13 W 14	<b>Section Width (mm)</b>	416 426 436
<b>Overall Diameter (mm)</b>	1 237	<b>Loaded Static Radius (mm)</b>	560
<b>Rolling Circumference (mm)</b>	3 700	<b>Speed radius index</b>	600
<b>EAN code</b>	8590341100153	<b>Water 75% (l)</b>	-

### LOAD CAPACITY PER TIRE

Tyre load at pressure (BAR)					Speed (km/h)
0,8	1	1,2	1,4	1,6	-
-	1 550	1 680	1 800	1 900	50
1 410	1 550	1 680	1 800	1 900	40
1 505	1 660	1 800	1 930	2 030	30
1 830	2 015	2 180	2 340	2 470	10