



420/85 R 24 137 A8 (137 B) RD-01 TL

- All-round standard tyres for a wide range of applications
- Balanced combination of features for various agricultural applications
- Very good grip and traction with much less slip
- Long service life thanks to the wear-resistant tread compound
- Large ground contact patch and lower operating pressure for less soil compaction

TECHNICAL DATA

Tyre size	420/85 R 24	Tread Pattern	RD-01
Tyre size alternative	16.9 R 24	Service description LI SS	137 A8 (137 B)
Type	TL	Permitted Rims	W 15 W 14 W 13
Section Width (mm)	470 460 450	Overall Diameter (mm)	1 318
Loaded Static Radius (mm)	576	Rolling Circumference (mm)	3 895
Speed radius index	625	EAN code	8590341099341
Water 75% (l)	240		

LOAD CAPACITY PER TIRE

Tyre load at pressure (BAR)											Speed (km/h)
0,6	0,8	1	1,2	1,4	1,6	2	2,4	3	4	4,4	-
-	-	1 845	2 000	2 145	2 300	-	-	-	-	-	50
-	1 675	1 845	2 000	2 145	2 300	-	-	-	-	-	40
1 595	1 795	1 970	2 140	2 295	2 460	-	-	-	-	-	30
1 940	2 175	2 395	2 600	2 790	2 990	3 450	-	-	-	-	10