



## 420/85 R 28 139 A8 (136 B) RD-01 TL

- All-round standard tyres for a wide range of applications
- Balanced combination of features for various agricultural applications
- Very good grip and traction with much less slip
- Long service life thanks to the wear-resistant tread compound
- Large ground contact patch and lower operating pressure for less soil compaction

### TECHNICAL DATA

<b>Tyre size</b>	420/85 R 28	<b>Tread Pattern</b>	RD-01
<b>Tyre size alternative</b>	16.9 R 28	<b>Service description LI SS</b>	139 A8 (136 B)
<b>Type</b>	TL	<b>Permitted Rims</b>	WE W14 W13
<b>Section Width (mm)</b>	449 439 429	<b>Overall Diameter (mm)</b>	1 428
<b>Loaded Static Radius (mm)</b>	635	<b>Rolling Circumference (mm)</b>	4 215
<b>Speed radius index</b>	675	<b>EAN code</b>	8590341099280
<b>Water 75% (l)</b>	250		

### LOAD CAPACITY PER TIRE

Tyre load at pressure (BAR)											Speed (km/h)
0,6	0,8	1	1,2	1,4	1,6	2	2,4	3	4	4,4	-
-	-	1 790	1 945	2 085	2 240	-	-	-	-	-	50
-	1 790	1 970	2 135	2 290	2 430	-	-	-	-	-	40
1 705	1 915	2 110	2 290	2 450	2 600	-	-	-	-	-	30
2 070	2 325	2 560	2 780	2 980	3 160	3 645	-	-	-	-	10