



420/85 R 30 140 A8 (137 B) RD-01 TL

- All-round standard tyres for a wide range of applications
- Balanced combination of features for various agricultural applications
- Very good grip and traction with much less slip
- Long service life thanks to the wear-resistant tread compound
- Large ground contact patch and lower operating pressure for less soil compaction

TECHNICAL DATA

Tyre size	420/85 R 30	Tread Pattern	RD-01
Tyre size alternative	16.9 R 30	Service description LI SS	140 A8 (137 B)
Type	TL	Permitted Rims	W 15 W 14 W 13
Section Width (mm)	444 434 424	Overall Diameter (mm)	1 475
Loaded Static Radius (mm)	670	Rolling Circumference (mm)	4 400
Speed radius index	700	EAN code	8590341099303
Water 75% (l)	270		

LOAD CAPACITY PER TIRE

Tyre load at pressure (BAR)											Speed (km/h)
0,6	0,8	1	1,2	1,4	1,6	2	2,4	3	4	4,4	-
-	-	1 850	2 005	2 150	2 300	-	-	-	-	-	50
-	1 845	2 030	2 205	2 365	2 500	-	-	-	-	-	40
1 760	1 975	2 175	2 360	2 530	2 675	-	-	-	-	-	30
2 140	2 400	2 640	2 865	3 075	3 250	3 750	-	-	-	-	10