



420/85 R 34 147 A8 (144 B) RD-01 TL

- All-round standard tyres for a wide range of applications
- Balanced combination of features for various agricultural applications
- Very good grip and traction with much less slip
- Long service life thanks to the wear-resistant tread compound
- Large ground contact patch and lower operating pressure for less soil compaction

TECHNICAL DATA

Tyre size	420/85 R 34	Tread Pattern	RD-01
Tyre size alternative	16.9 R 34	Service description LI SS	147 A8 (144 B)
Type	TL	Permitted Rims	W 15 W 14 W 13
Section Width (mm)	443 433 423	Overall Diameter (mm)	1 571
Loaded Static Radius (mm)	712	Rolling Circumference (mm)	4 715
Speed radius index	750	EAN code	8590341099549
Water 75% (l)	290		

LOAD CAPACITY PER TIRE

Tyre load at pressure (BAR)									Speed (km/h)
0,6	0,8	1	1,2	1,4	1,6	2	2,4	3	-
-	-	2 155	2 335	2 505	2 650	2 905	3 075	-	50
-	1 955	2 155	2 335	2 505	2 650	2 905	3 075	-	40
1 865	2 095	2 305	2 500	2 680	2 835	3 110	3 290	-	30
2 265	2 545	2 800	3 035	3 255	3 445	3 775	4 000	4 350	10
-	1 720	1 896	2 055	2 204	2 332	2 556	2 706	-	40 Dual