



420/85 R 38 144 A8 (141 B) RD-01 TL

- All-round standard tyres for a wide range of applications
- Balanced combination of features for various agricultural applications
- Very good grip and traction with much less slip
- Long service life thanks to the wear-resistant tread compound
- Large ground contact patch and lower operating pressure for less soil compaction

TECHNICAL DATA

Tyre size	420/85 R 38	Tread Pattern	RD-01
Tyre size alternative	16.9 R 38	Service description LI SS	144 A8 (141 B)
Type	TL	Permitted Rims	W 15 W 14 W 13
Section Width (mm)	446 436 426	Overall Diameter (mm)	1 675
Loaded Static Radius (mm)	764	Rolling Circumference (mm)	5 020
Speed radius index	800	EAN code	8590341098863
Water 75% (l)	320		

LOAD CAPACITY PER TIRE

Tyre load at pressure (BAR)											Speed (km/h)
0,6	0,8	1	1,2	1,4	1,6	2	2,4	3	4	4,4	-
-	-	2 070	2 240	2 400	2 575	-	-	-	-	-	50
-	2 065	2 270	2 465	2 640	2 800	-	-	-	-	-	40
1 965	2 210	2 430	2 635	2 830	3 000	-	-	-	-	-	30
2 390	2 685	2 955	3 205	3 435	3 640	4 200	-	-	-	-	10