



440/65 R 24 128 D (131 A8) RD-03 TL

- Reduced soil compaction thanks to large ground contact area and optimal pressure distribution
- Up to 40% higher tension force compared to standard tyres
- High load capacity due to the wide design and the large volume of air
- Outstanding grip and tractive force ensure less slip and much lower fuel consumption
- Maximum speed of 65 km/h on roads, high driving comfort and easy handling

TECHNICAL DATA

Tyre size	440/65 R 24	Tread Pattern	RD-03
Service description LI SS	128 D (131 A8)	Type	TL
Permitted Rims	W 14 L W 13 W 12	Section Width (mm)	448 438 428
Overall Diameter (mm)	1 190	Loaded Static Radius (mm)	535
Rolling Circumference (mm)	3 560	Speed radius index	575
EAN code	8590341100832	Water 75% (l)	185

LOAD CAPACITY PER TIRE

Tyre load at pressure (BAR)										Speed (km/h)
0,4	0,6	0,8	1	1,2	1,4	1,6	2	2,4	3	-
-	-	-	1 400	1 530	1 670	1 800	-	-	-	65
-	-	1 325	1 470	1 610	1 750	1 890	-	-	-	50
-	1 215	1 380	1 535	1 675	1 830	1 950	-	-	-	40
-	1 280	1 450	1 610	1 760	1 920	2 070	-	-	-	30
1 330	1 555	1 765	1 960	2 145	2 335	2 520	2 955	-	-	10