



440/65 R 28 131 D (134 A8) RD-03 TL

- Reduced soil compaction thanks to large ground contact area and optimal pressure distribution
- Up to 40% higher tension force compared to standard tyres
- High load capacity due to the wide design and the large volume of air
- Outstanding grip and tractive force ensure less slip and much lower fuel consumption
- Maximum speed of 65 km/h on roads, high driving comfort and easy handling

TECHNICAL DATA

Tyre size	440/65 R 28	Tread Pattern	RD-03
Service description LI SS	131 D (134 A8)	Type	TL
Permitted Rims	W 14 L W 13 W 12	Section Width (mm)	445 435 425
Overall Diameter (mm)	1 295	Loaded Static Radius (mm)	588
Rolling Circumference (mm)	3 882	Speed radius index	625
EAN code	8590341100863	Water 75% (l)	200

LOAD CAPACITY PER TIRE

Tyre load at pressure (BAR)										Speed (km/h)
0,4	0,6	0,8	1	1,2	1,4	1,6	2	2,4	3	-
-	-	-	1 505	1 645	1 800	1 950	-	-	-	65
-	-	1 425	1 580	1 725	1 890	2 050	-	-	-	50
-	1 305	1 485	1 650	1 800	1 970	2 120	-	-	-	40
-	1 375	1 560	1 730	1 890	2 070	2 245	-	-	-	30
1 430	1 670	1 895	2 110	2 305	2 520	2 730	3 205	-	-	10