



# 460/85 R 30 145 A8 (142 B) RD-01 TL

- All-round standard tyres for a wide range of applications
- Balanced combination of features for various agricultural applications
- Very good grip and traction with much less slip
- Long service life thanks to the wear-resistant tread compound
- Large ground contact patch and lower operating pressure for less soil compaction

## TECHNICAL DATA

Tyre size	460/85 R 30	Tread Pattern	RD-01
Tyre size alternative	18.4 R 30	Service description LI SS	145 A8 (142 B)
Type	TL	Permitted Rims	W 16 W 15 W 14
Section Width (mm)	490 480 470	Overall Diameter (mm)	1 540
Loaded Static Radius (mm)	685	Rolling Circumference (mm)	4 582
Speed radius index	725	EAN code	8590341099518
Water 75% (l)	340		

## LOAD CAPACITY PER TIRE

Tyre load at pressure (BAR)											Speed (km/h)
0,6	0,8	1	1,2	1,4	1,6	2	2,4	3	4	4,4	-
-	-	2 130	2 310	2 475	2 650	-	-	-	-	-	50
-	2 130	2 340	2 540	2 720	2 900	-	-	-	-	-	40
2 030	2 280	2 510	2 720	2 910	3 100	-	-	-	-	-	30
2 460	2 760	3 040	3 300	3 540	3 770	4 350	-	-	-	-	10