



460/85 R 34 147 A8 (144 B) RD-01 TL

- All-round standard tyres for a wide range of applications
- Balanced combination of features for various agricultural applications
- Very good grip and traction with much less slip
- Long service life thanks to the wear-resistant tread compound
- Large ground contact patch and lower operating pressure for less soil compaction

TECHNICAL DATA

Tyre size	460/85 R 34	Tread Pattern	RD-01
Tyre size alternative	18.4 R 34	Service description LI SS	147 A8 (144 B)
Type	TL	Permitted Rims	W 16 W 15 W 14
Section Width (mm)	488 478 468	Overall Diameter (mm)	1 624
Loaded Static Radius (mm)	727	Rolling Circumference (mm)	4 847
Speed radius index	775	EAN code	8590341099556
Water 75% (l)	380		

LOAD CAPACITY PER TIRE

Tyre load at pressure (BAR)											Speed (km/h)
0,6	0,8	1	1,2	1,4	1,6	2	2,4	3	4	4,4	-
-	-	2 250	2 445	2 620	2 800	-	-	-	-	-	50
-	2 250	2 475	2 685	2 880	3 075	-	-	-	-	-	40
2 145	2 405	2 650	2 875	3 080	3 290	-	-	-	-	-	30
2 605	2 925	3 220	3 490	3 745	4 000	4 615	-	-	-	-	10