



480/65 R 24 133 D (136 A8) RD-03 TL

- Reduced soil compaction thanks to large ground contact area and optimal pressure distribution
- Up to 40% higher tension force compared to standard tyres
- High load capacity due to the wide design and the large volume of air
- Outstanding grip and tractive force ensure less slip and much lower fuel consumption
- Maximum speed of 65 km/h on roads, high driving comfort and easy handling

TECHNICAL DATA

Tyre size	480/65 R 24	Tread Pattern	RD-03
Service description LI SS	133 D (136 A8)	Type	TL
Permitted Rims	W 15 L W 14 L W 13	Section Width (mm)	485 475 465
Overall Diameter (mm)	1 239	Loaded Static Radius (mm)	545
Rolling Circumference (mm)	3 670	Speed radius index	600
EAN code	8590341100849	Water 75% (l)	210

LOAD CAPACITY PER TIRE

Tyre load at pressure (BAR)										Speed (km/h)
0,4	0,6	0,8	1	1,2	1,4	1,6	2	2,4	3	-
-	-	-	1 605	1 755	1 910	2 060	-	-	-	65
-	-	1 515	1 685	1 840	2 005	2 165	-	-	-	50
-	1 395	1 580	1 755	1 920	2 090	2 240	-	-	-	40
-	1 465	1 660	1 845	2 015	2 195	2 370	-	-	-	30
1 525	1 780	2 020	2 245	2 455	2 675	2 885	3 385	-	-	10