



## 480/70 R 34 143 A8 (143 B) RD-02 TL

- Reduced ground compression thanks to a larger ground contact area
- Excellent transmission of power due to greater grip and traction
- High load capacity with stable and safe handling on the road
- Improved driving comfort due to flexible sidewalls
- Longer service life coupled with reduced fuel consumption for low operational costs

### TECHNICAL DATA

<b>Tyre size</b>	480/70 R 34	<b>Tread Pattern</b>	RD-02
<b>Service description LI SS</b>	143 A8 (143 B)	<b>Type</b>	TL
<b>Permitted Rims</b>	W 15 L W 16 L W 14 L	<b>Section Width (mm)</b>	487 497 477
<b>Overall Diameter (mm)</b>	1 584	<b>Loaded Static Radius (mm)</b>	708
<b>Rolling Circumference (mm)</b>	4 710	<b>Speed radius index</b>	750
<b>EAN code</b>	8590341099631	<b>Water 75% (l)</b>	310

### LOAD CAPACITY PER TYRE

Tyre load at pressure (BAR)							Speed (km/h)
0,6	0,8	1	1,2	1,4	1,6	2	-
-	-	2 235	2 425	2 600	2 725	-	50
-	2 030	2 235	2 425	2 600	2 725	-	40
1 935	2 170	2 390	2 595	2 780	2 915	-	30
2 350	2 640	2 905	3 150	3 380	3 545	4 090	10