



480/80 R 42 151 A8 (151 B) RD-01 TL

- All-round standard tyres for a wide range of applications
- Balanced combination of features for various agricultural applications
- Very good grip and traction with much less slip
- Long service life thanks to the wear-resistant tread compound
- Large ground contact patch and lower operating pressure for less soil compaction

TECHNICAL DATA

Tyre size	480/80 R 42	Tread Pattern	RD-01
Tyre size alternative	-	Service description LI SS	151 A8 (151 B)
Type	TL	Permitted Rims	W 16 W 15 W 14
Section Width (mm)	500 500 490	Overall Diameter (mm)	1 840
Loaded Static Radius (mm)	821	Rolling Circumference (mm)	5 460
Speed radius index	875	EAN code	8590341099785
Water 75% (l)	440		

LOAD CAPACITY PER TIRE

Tyre load at pressure (BAR)									Speed (km/h)
0,6	0,8	1	1,2	1,4	1,6	2	2,4	3	-
-	-	2 565	2 805	3 125	3 450	-	-	-	50
-	2 305	2 565	2 805	3 125	3 450	-	-	-	40
2 170	2 465	2 745	3 000	3 345	3 690	-	-	-	30
2 840	3 230	3 590	3 925	4 375	4 830	5 175	-	-	10
-	2 028	2 257	2 468	2 750	3 036	-	-	-	40 Dual