



## 500/60 - 22.5 16 AS-Impl 08 TL

Cultor implement tyres are designed for their specific main application. All profiles unify the following benefits:

- Long service life through low-wear tread compound
- High puncture resistance by optimised construction

### TECHNICAL DATA

|                                  |               |                                   |            |
|----------------------------------|---------------|-----------------------------------|------------|
| <b>Tyre size</b>                 | 500/60 - 22.5 | <b>Tread Pattern</b>              | AS-Impl 08 |
| <b>Tyre size alternative</b>     | -             | <b>Ply rating</b>                 | 16         |
| <b>Service description LI SS</b> | -             | <b>Type</b>                       | TL         |
| <b>Tube</b>                      | -             | <b>Permitted Rims</b>             | 16.00x22.5 |
| <b>Section Width (mm)</b>        | 503           | <b>Overall Diameter (mm)</b>      | 1 192      |
| <b>Loaded Static Radius (mm)</b> | 519           | <b>Rolling Circumference (mm)</b> | 3 504      |
| <b>EAN code</b>                  | 8590341059970 |                                   |            |

### LOAD CAPACITY PER TIRE -

| Tyre load at pressure (BAR) | Speed (km/h) |
|-----------------------------|--------------|
| <b>3</b>                    | -            |
| 6 125                       | 10           |
| 5 515                       | 20           |
| 4 900                       | 30           |
| 4 375                       | 40           |
| 3 940                       | 50           |

### LOAD CAPACITY PER TIRE -

| Tyre load at pressure (BAR) | Speed (km/h) |
|-----------------------------|--------------|
| <b>3</b>                    | -            |
| 4 305                       | 10           |
| 3 875                       | 20           |
| 3 445                       | 30           |
| 3 075                       | 40           |
| 2 770                       | 50           |