



## 520/70 R 38 150 A8 (150 B) RD-02 TL

- Reduced ground compression thanks to a larger ground contact area
- Excellent transmission of power due to greater grip and traction
- High load capacity with stable and safe handling on the road
- Improved driving comfort due to flexible sidewalls
- Longer service life coupled with reduced fuel consumption for low operational costs

### TECHNICAL DATA

<b>Tyre size</b>	520/70 R 38	<b>Tread Pattern</b>	RD-02
<b>Service description LI SS</b>	150 A8 (150 B)	<b>Type</b>	TL
<b>Permitted Rims</b>	W 16 L W 18 L W 15 L	<b>Section Width (mm)</b>	524 544 514
<b>Overall Diameter (mm)</b>	1 761	<b>Loaded Static Radius (mm)</b>	787
<b>Rolling Circumference (mm)</b>	5 238	<b>Speed radius index</b>	825
<b>EAN code</b>	8590341099655	<b>Water 75% (l)</b>	395

### LOAD CAPACITY PER TIRE

Tyre load at pressure (BAR)							Speed (km/h)
0,6	0,8	1	1,2	1,4	1,6	2	-
-	-	2 600	2 830	3 060	3 350	-	50
-	2 380	2 600	2 830	3 060	3 350	-	40
2 300	2 550	2 780	3 030	3 270	3 590	-	30
2 800	3 090	3 380	3 680	3 980	4 360	5 030	10