



520/85 R 42 162 A8 (162 B) RD-01 TL

- All-round standard tyres for a wide range of applications
- Balanced combination of features for various agricultural applications
- Very good grip and traction with much less slip
- Long service life thanks to the wear-resistant tread compound
- Large ground contact patch and lower operating pressure for less soil compaction

TECHNICAL DATA

Tyre size	520/85 R 42	Tread Pattern	RD-01
Tyre size alternative	20.8 R 42	Service description LI SS	162 A8 (162 B)
Type	TL	Permitted Rims	W 16 W 18
Section Width (mm)	537 557	Overall Diameter (mm)	1 950
Loaded Static Radius (mm)	891	Rolling Circumference (mm)	5 845
Speed radius index	925	EAN code	8590341100733
Water 75% (l)	580		

LOAD CAPACITY PER TIRE

Tyre load at pressure (BAR)										Speed (km/h)	
0,6	0,8	1	1,2	1,4	1,6	2	2,4	3	4	4,4	-
-	-	3 300	3 575	3 840	4 075	4 520	4 750	-	-	-	50
-	2 995	3 300	3 575	3 840	4 075	4 520	4 750	-	-	-	40
2 860	3 205	3 530	3 825	4 100	4 360	4 835	5 085	-	-	-	30
3 470	3 895	4 285	4 650	4 990	5 300	5 875	6 175	7 125	-	-	10