



540/65 R 24 140 D (143 A8) RD-03 TL

- Reduced soil compaction thanks to large ground contact area and optimal pressure distribution
- Up to 40% higher tension force compared to standard tyres
- High load capacity due to the wide design and the large volume of air
- Outstanding grip and tractive force ensure less slip and much lower fuel consumption
- Maximum speed of 65 km/h on roads, high driving comfort and easy handling

TECHNICAL DATA

| | | | |
|-----------------------------------|----------------------------|----------------------------------|-------------------|
| Tyre size | 540/65 R 24 | Tread Pattern | RD-03 |
| Service description LI SS | 140 D (143 A8) | Type | TL |
| Permitted Rims | W 16 L W 18 L W 15 L | Section Width (mm) | 527 547 517 |
| Overall Diameter (mm) | 1 300 | Loaded Static Radius (mm) | 572 |
| Rolling Circumference (mm) | 3 839 | Speed radius index | 625 |
| EAN code | 8590341100856 | Water 75% (l) | 300 |

LOAD CAPACITY PER TIRE

| Tyre load at pressure (BAR) | | | | | | | | | | Speed (km/h) |
|-----------------------------|-------|-------|-------|-------|-------|-------|-------|-----|---|--------------|
| 0,4 | 0,6 | 0,8 | 1 | 1,2 | 1,4 | 1,6 | 2 | 2,4 | 3 | - |
| - | - | - | 1 930 | 2 110 | 2 310 | 2 500 | - | - | - | 65 |
| - | - | 1 825 | 2 025 | 2 215 | 2 425 | 2 625 | - | - | - | 50 |
| - | 1 675 | 1 900 | 2 115 | 2 310 | 2 525 | 2 725 | - | - | - | 40 |
| - | 1 760 | 1 995 | 2 220 | 2 425 | 2 655 | 2 875 | - | - | - | 30 |
| 1 835 | 2 140 | 2 430 | 2 700 | 2 950 | 3 230 | 3 500 | 4 105 | - | - | 10 |