



## 540/65 R 28 142 D (145 A8) RD-03 TL

- Reduced soil compaction thanks to large ground contact area and optimal pressure distribution
- Up to 40% higher tension force compared to standard tyres
- High load capacity due to the wide design and the large volume of air
- Outstanding grip and tractive force ensure less slip and much lower fuel consumption
- Maximum speed of 65 km/h on roads, high driving comfort and easy handling

### TECHNICAL DATA

<b>Tyre size</b>	540/65 R 28	<b>Tread Pattern</b>	RD-03
<b>Service description LI SS</b>	142 D (145 A8)	<b>Type</b>	TL
<b>Permitted Rims</b>	W 16 L W 18 L W 15 L	<b>Section Width (mm)</b>	520 540 510
<b>Overall Diameter (mm)</b>	1 402	<b>Loaded Static Radius (mm)</b>	622
<b>Rolling Circumference (mm)</b>	4 150	<b>Speed radius index</b>	675
<b>EAN code</b>	8590341100887	<b>Water 75% (l)</b>	315

### LOAD CAPACITY PER TIRE

Tyre load at pressure (BAR)										Speed (km/h)
0,4	0,6	0,8	1	1,2	1,4	1,6	2	2,4	3	-
-	-	-	2 065	2 255	2 455	2 650	-	-	-	65
-	-	1 950	2 165	2 365	2 580	2 785	-	-	-	50
-	1 790	2 035	2 260	2 470	2 690	2 900	-	-	-	40
-	1 880	2 135	2 375	2 595	2 825	3 050	-	-	-	30
1 960	2 290	2 600	2 890	3 155	3 440	3 710	4 355	-	-	10