



540/65 R 34 145 D (148 A8) RD-03 TL

- Reduced soil compaction thanks to large ground contact area and optimal pressure distribution
- Up to 40% higher tension force compared to standard tyres
- High load capacity due to the wide design and the large volume of air
- Outstanding grip and tractive force ensure less slip and much lower fuel consumption
- Maximum speed of 65 km/h on roads, high driving comfort and easy handling

TECHNICAL DATA

Tyre size	540/65 R 34	Tread Pattern	RD-03
Service description LI SS	145 D (148 A8)	Type	TL
Permitted Rims	W 16 L W 18 L W 15 L	Section Width (mm)	523 543 513
Overall Diameter (mm)	1 579	Loaded Static Radius (mm)	710
Rolling Circumference (mm)	4 710	Speed radius index	750
EAN code	8590341100924	Water 75% (l)	360

LOAD CAPACITY PER TIRE

Tyre load at pressure (BAR)										Speed (km/h)
0,4	0,6	0,8	1	1,2	1,4	1,6	2	2,4	3	-
-	-	-	2 255	2 465	2 690	2 900	-	-	-	65
-	-	2 130	2 370	2 590	2 820	3 045	-	-	-	50
-	1 960	2 225	2 470	2 700	2 945	3 150	-	-	-	40
-	2 055	2 335	2 595	2 835	3 090	3 335	-	-	-	30
2 145	2 505	2 845	3 160	3 450	3 765	4 060	4 765	-	-	10