



540/65 R 38 147 D (150 A8) RD-03 TL

- Reduced soil compaction thanks to large ground contact area and optimal pressure distribution
- Up to 40% higher tension force compared to standard tyres
- High load capacity due to the wide design and the large volume of air
- Outstanding grip and tractive force ensure less slip and much lower fuel consumption
- Maximum speed of 65 km/h on roads, high driving comfort and easy handling

TECHNICAL DATA

Tyre size	540/65 R 38	Tread Pattern	RD-03
Service description LI SS	147 D (150 A8)	Type	TL
Permitted Rims	W 16 L W 18 L W 15 L	Section Width (mm)	522 542 512
Overall Diameter (mm)	1 681	Loaded Static Radius (mm)	752
Rolling Circumference (mm)	5 003	Speed radius index	800
EAN code	8590341100948	Water 75% (l)	420

LOAD CAPACITY PER TIRE

Tyre load at pressure (BAR)										Speed (km/h)
0,4	0,6	0,8	1	1,2	1,4	1,6	2	2,4	3	-
-	-	-	2 380	2 600	2 845	3 075	-	-	-	65
-	-	2 250	2 500	2 730	2 985	3 230	-	-	-	50
-	2 065	2 345	2 605	2 850	3 115	3 350	-	-	-	40
-	2 170	2 465	2 765	2 990	3 270	3 535	-	-	-	30
2 260	2 640	3 000	3 330	3 640	3 980	4 305	5 050	-	-	10