



## 550/60 - 22.5 16 AS-Impl 08 TL

Cultor implement tyres are designed for their specific main application. All profiles unify the following benefits:

- Long service life through low-wear tread compound
- High puncture resistance by optimised construction

### TECHNICAL DATA

<b>Tyre size</b>	550/60 - 22.5	<b>Tread Pattern</b>	AS-Impl 08
<b>Tyre size alternative</b>	-	<b>Ply rating</b>	16
<b>Service description LI SS</b>	-	<b>Type</b>	TL
<b>Tube</b>	-	<b>Permitted Rims</b>	16.00x22.5
<b>Section Width (mm)</b>	537	<b>Overall Diameter (mm)</b>	1 254
<b>Loaded Static Radius (mm)</b>	542	<b>Rolling Circumference (mm)</b>	3 687
<b>EAN code</b>	8590341059994		

### LOAD CAPACITY PER TIRE -

Tyre load at pressure (BAR)	Speed (km/h)
<b>2,8</b>	-
6 825	10
6 145	20
5 460	30
4 875	40
4 390	50

### LOAD CAPACITY PER TIRE -

Tyre load at pressure (BAR)	Speed (km/h)
<b>2,8</b>	-
4 830	10
4 345	20
3 865	30
3 450	40
3 105	50