



580/70 R 38 155 A8 (155 B) RD-02 TL

- Reduced ground compression thanks to a larger ground contact area
- Excellent transmission of power due to greater grip and traction
- High load capacity with stable and safe handling on the road
- Improved driving comfort due to flexible sidewalls
- Longer service life coupled with reduced fuel consumption for low operational costs

TECHNICAL DATA

Tyre size	580/70 R 38	Tread Pattern	RD-02
Service description LI SS	155 A8 (155 B)	Type	TL
Permitted Rims	W 18 L	Section Width (mm)	575
Overall Diameter (mm)	1 846	Loaded Static Radius (mm)	824
Rolling Circumference (mm)	5 460	Speed radius index	875
EAN code	8590341100177	Water 75% (l)	-

LOAD CAPACITY PER TIRE

Tyre load at pressure (BAR)							Speed (km/h)
0,6	0,8	1	1,2	1,4	1,6	2	-
-	-	3 145	3 410	3 655	3 875	-	50
-	2 855	3 145	3 410	3 655	3 875	-	40
2 720	3 060	3 365	3 650	3 915	4 145	-	30
3 130	3 515	3 870	4 195	4 500	4 770	-	20
3 310	3 715	4 090	4 435	4 755	5 040	5 815	10