



600/65 R 28 147 D (150 A8) RD-03 TL

- Reduced soil compaction thanks to large ground contact area and optimal pressure distribution
- Up to 40% higher tension force compared to standard tyres
- High load capacity due to the wide design and the large volume of air
- Outstanding grip and tractive force ensure less slip and much lower fuel consumption
- Maximum speed of 65 km/h on roads, high driving comfort and easy handling

TECHNICAL DATA

Tyre size	600/65 R 28	Tread Pattern	RD-03
Service description LI SS	147 D (150 A8)	Type	TL
Permitted Rims	W 18 L DW 18 L W 16 L	Section Width (mm)	597 597 577
Overall Diameter (mm)	1 475	Loaded Static Radius (mm)	640
Rolling Circumference (mm)	4 340	Speed radius index	700
EAN code	8590341100894	Water 75% (l)	400

LOAD CAPACITY PER TIRE

Tyre load at pressure (BAR)										Speed (km/h)
0,4	0,6	0,8	1	1,2	1,4	1,6	2	2,4	3	-
-	-	-	2 430	2 660	2 875	3 075	-	-	-	65
-	-	2 300	2 555	2 790	3 020	3 230	-	-	-	50
-	2 110	2 395	2 665	2 910	3 145	3 350	-	-	-	40
-	2 220	2 515	2 795	3 055	3 305	3 535	-	-	-	30
2 310	2 700	3 065	3 405	3 720	4 025	4 305	5 050	-	-	10