



600/65 R 38 153 D (156 A8) RD-03 TL

- Reduced soil compaction thanks to large ground contact area and optimal pressure distribution
- Up to 40% higher tension force compared to standard tyres
- High load capacity due to the wide design and the large volume of air
- Outstanding grip and tractive force ensure less slip and much lower fuel consumption
- Maximum speed of 65 km/h on roads, high driving comfort and easy handling

TECHNICAL DATA

Tyre size	600/65 R 38	Tread Pattern	RD-03
Service description LI SS	153 D (156 A8)	Type	TL
Permitted Rims	W 18 L DW 18 L W 16 L	Section Width (mm)	588 588 568
Overall Diameter (mm)	1 742	Loaded Static Radius (mm)	781
Rolling Circumference (mm)	5 212	Speed radius index	825
EAN code	8590341100955	Water 75% (l)	500

LOAD CAPACITY PER TIRE

Tyre load at pressure (BAR)										Speed (km/h)
0,4	0,6	0,8	1	1,2	1,4	1,6	2	2,4	3	-
-	-	-	2 795	3 050	3 355	3 650	-	-	-	65
-	-	2 640	2 935	3 205	3 525	3 835	-	-	-	50
-	2 425	2 755	3 060	3 340	3 675	4 000	-	-	-	40
-	2 545	2 890	3 210	3 510	3 860	4 200	-	-	-	30
2 655	3 100	3 520	3 910	4 275	4 695	5 110	5 995	-	-	10