



## 650/65 R 42 165 D (168 A8) RD-03 TL

- Reduced soil compaction thanks to large ground contact area and optimal pressure distribution
- Up to 40% higher tension force compared to standard tyres
- High load capacity due to the wide design and the large volume of air
- Outstanding grip and tractive force ensure less slip and much lower fuel consumption
- Maximum speed of 65 km/h on roads, high driving comfort and easy handling

### TECHNICAL DATA

<b>Tyre size</b>	650/65 R 42	<b>Tread Pattern</b>	RD-03
<b>Service description LI SS</b>	165 D (168 A8)	<b>Type</b>	TL
<b>Permitted Rims</b>	<b>DW 20 B</b> DW 18 L	<b>Section Width (mm)</b>	635 615
<b>Overall Diameter (mm)</b>	1 926	<b>Loaded Static Radius (mm)</b>	868
<b>Rolling Circumference (mm)</b>	5 767	<b>Speed radius index</b>	925
<b>EAN code</b>	8590341100993	<b>Water 75% (l)</b>	650

### LOAD CAPACITY PER TIRE

Tyre load at pressure (BAR)										Speed (km/h)
0,4	0,6	0,8	1	1,2	1,4	1,6	2	2,4	3	-
-	-	-	3 310	3 615	3 960	4 290	4 765	5 150	-	65
-	-	3 125	3 475	3 795	4 155	4 505	5 005	5 410	-	50
-	2 875	3 260	3 625	3 960	4 335	4 700	5 220	5 600	-	40
-	3 015	3 425	3 805	4 160	4 555	4 935	5 480	5 925	-	30
3 145	3 675	4 170	4 635	5 065	5 545	6 005	6 675	7 210	8 460	10