



710/70 R 38 166 D (169 A8) RD-03 TL

- Reduced soil compaction thanks to large ground contact area and optimal pressure distribution
- Up to 40% higher tension force compared to standard tyres
- High load capacity due to the wide design and the large volume of air
- Outstanding grip and tractive force ensure less slip and much lower fuel consumption
- Maximum speed of 65 km/h on roads, high driving comfort and easy handling

TECHNICAL DATA

Tyre size	710/70 R 38	Tread Pattern	RD-03
Service description LI SS	166 D (169 A8)	Type	TL
Permitted Rims	DW 23 B	Section Width (mm)	703
Overall Diameter (mm)	1 922	Loaded Static Radius (mm)	848
Rolling Circumference (mm)	5 693	Speed radius index	925
EAN code	8590341100986	Water 75% (l)	800

LOAD CAPACITY PER TIRE

Tyre load at pressure (BAR)										Speed (km/h)
0,4	0,6	0,8	1	1,2	1,4	1,6	2	2,4	3	-
-	-	-	3 975	4 345	4 825	5 300	-	-	-	65
-	-	3 755	4 175	4 565	5 065	5 565	-	-	-	50
-	3 445	3 915	4 350	4 760	5 280	5 800	-	-	-	40
-	3 620	4 110	4 570	5 000	5 550	6 095	-	-	-	30
3 765	4 405	5 005	5 565	6 085	6 755	7 420	8 705	-	-	10